



GOOD WATER WAREHOUSE, INC.

U.S.A - Corporate Office

Call: 714-441-2893
 Fax: 714-441-0525
 Toll Free: 800-749-0252
 Toll Free Fax: 800-749-0331
 sales@goodwaterwarehouse.com

U.S.A - Santa Barbara Office

Tel: 805-683-8889
 Fax: 805-683-0102

Canada - Ontario

Call: 905-868-9287
 Fax: 905-830-0512
 Toll Free: 888-868-9287

Canada - Alberta

Call: 403-252-7972
 Fax: 403-252-3462
 Toll Free: 888-668-1234
 Toll Free Fax: 888-227-3291
 canadasales@goodwaterwarehouse.com

SUPPLYING THE WORLD - YOUR SINGLE SOURCE SUPPLIER

Reverse Osmosis System
 model: FRAME MOUNT VERTICAL
 1,600 to 14,400 gpd

STANDARD FEATURES:

- ✓ High efficiency membrane
- ✓ Stainless steel membrane vessel
- ✓ Powder-coated steel frame
- ✓ Stainless steel multi-stage pump
- ✓ TEFC motor
- ✓ Throttle Valve
- ✓ Liquid-filled system pressure gauge and inlet/outlet pre-filter gauges
- ✓ Adjstbl SS Waste/Recycle needle valves
- ✓ Product and Waste Flow Meters
- ✓ Float switch for open storage tank
- ✓ SS Feed water inlet solenoid valve
- ✓ Feed water low pressure switch
- ✓ 20" BB 5 micron sediment pre-filter
- ✓ 110volt—60hz or 220v-60hz

FMV-8S additional standard features:

Recycle Valve, Recycle Flow Meter



STANDARD ELECTRICAL CONTROLS:

- ✓ 4-line LCD display
- ✓ Keypad
- ✓ Menu system
- ✓ Permeate temp display
- ✓ TDS monitor with probe
- ✓ Tank full
- ✓ Low pressure
- ✓ Hour meter
- ✓ Time delay start
- ✓ System On/Off
- ✓ Dual-level float switch

Options:

- ▶ Nanofiltration membrane
- ▶ Blending valve
- ▶ Recycle flow meter
- ▶ Auto hourly flush
- ▶ Pre-Treat Lock-out
- ▶ Feed water TDS monitor
- ▶ Product diversion
- ▶ Permeate purge
- ▶ Hi-pressure cut-off
- ▶ 3ph motor w/IEC motor contactor w/overload relay
- ▶ 50hz motor
- ▶ Electrical outlet for anti-scalant pump

MODEL	*GPD	Feed TDS 2,000 BELOW ABOVE	Membrane 4" x 40" Qty.	motor	Operating pressure	110v- 60hz AMPS	220v- 60hz-1ph AMPS	RECOVERY RATE % * Up to:	PIPING inlet waste prod	DIMENSIONS weight lbs.
FMV-1S FMV-1N FMV-1	1,800+ 1,800+ 1,600+	● ● ●	1 LE 1 NANO 1 BW	1hp 1hp 1.5hp	150psi 75-100psi 200psi	11.6 11.6 20.0	5.8 5.8 10.4	70% 80% 70%	3/4" FPT 1/2" FPT 1/2" FPT	24"x 29"x 53"H 140 lbs.
FMV-2S FMV-2N FMV-2	3,600+ 3,600+ 3,170+	● ● ●	2 LE 2 NANO 2 BW	1hp 1hp 1.5hp	150psi 75-100psi 200psi	11.6 11.6 20.0	5.8 5.8 10.4	70% 80% 70%	3/4" FPT 1/2" FPT 1/2" FPT	30"x 30"x 53"H 166 lbs.
FMV-3S FMV-3N FMV-3	5,400+ 5,400+ 4,750+	● ● ●	3 LE 3 NANO 3 BW	1hp 1hp 2hp	150psi 75-100psi 200psi	11.6 11.6 20.0	5.8 5.8 10.4	70% 80% 70%	3/4" FPT 1/2" FPT 1/2" FPT	30"x 30"x 53"H 194 lbs.
FMV-4S FMV-4N FMV-4	7,200+ 7,200+ 6,340+	● ● ●	4 LE 4 NANO 4 BW	2hp 2hp 3hp	150psi 75-100psi 200psi	19.2 19.2 n/a	9.8 9.8 13	70% 80% 70%	3/4" FPT 1/2" FPT 1/2" FPT	30"x 30"x 56"H 236 lbs.
FMV-5S FMV-5N FMV-5	9,000+ 9,000+ 7,900+	● ● ●	5 LE 5 NANO 5 BW	2hp 2hp 3hp	150psi 75-100psi 200psi	19.2 19.2 n/a	9.8 9.8 13	70% 80% 70%	3/4" FPT 1/2" FPT 1/2" FPT	30"x 30"x 56"H 267 lbs.
FMV-6S FMV-6N FMV-6	10,800+ 10,800+ 9,500+	● ● ●	6 LE 6 NANO 6 BW	2hp 2hp 3hp	150psi 75-100psi 200psi	19.2 19.2 n/a	9.8 9.8 13	70% 80% 70%	3/4" FPT 1/2" FPT 1/2" FPT	30"x 30"x 56"H 293 lbs.
FMV-8S FMV-8N	14,400+ 14,400+	● ●	8 LE 8 NANO	3hp 3hp	150psi 75-100psi	n/a n/a	13 13	70% 80%	1" FPT 1/2" FPT 3/4" FPT	30"x 40"x 56"H 320 lbs